



Model 3900

File Number: E352175



COMPANY

GUANGZHOU BAIZHUANG NEW MATERIALS CO LTD

No 8 Shangwei Dongyi Road, Shangtang Village
Shitan Town, Zengcheng District
Guangzhou, Guangdong 511328 China

MODEL INFO

3900
Silicone "Room Temperature Vulcanizing" (RTV), furnished as two liquid components

FLAMMABILITY PROPERTIES	额定值	测试方法
Flammability		ANSI/UL 94
1.5 mm, Color: WT, GY	V-0	
3.0 mm, Color: WT, GY, BK	V-0	
ISO/IEC FLAMMABILITY PROPERTIES	额定值	测试方法
Flammability		IEC 60695-11-10
1.5 mm, Color: WT, GY	V-0	
3.0 mm, Color: WT, GY, BK	V-0	
THERMAL PROPERTIES	额定值	测试方法
Relative Thermal Index - Electrical Strength		UL 746B
1.5 mm	105 °C	
3.0 mm	105 °C	
Relative Thermal Index - Mechanical Impact		UL 746B
1.5 mm	105 °C	
3.0 mm	105 °C	

Relative Thermal Index - Mechanical Strength		UL 746B
1.5 mm	105 °C	
3.0 mm	105 °C	

Report Date: 2014-08-19
Revision Date: 2019-05-10

并不是所有出现在本数据库中的公司名称和产品都满足了UL 跟踪检验服务的要求。只有带有 UL 标志的产品，才应该被视为经过 UL 认证，并满足UL 跟踪检验服务的要求。注意查看产品上的标志。

UL 允许在线认证目录中所含材料的复制遵循以下条件：1.指南信息、装配、构造、设计、系统和/或认证（文件）必须在不篡改任何数据（或图纸）的情况下完整且无误导性地呈现。2.“经 UL 允许从在线认证目录转载”声明必须出现在所摘取材料的邻近位置。此外，转载材料必须包含以下格式的版权声明：“©2024 UL LLC.”