



Model 6800A/B
File Number: E352175



COMPANY

GUANGZHOU BAIZHUANG NEW MATERIALS CO LTD
No 8 Shangwei Dongyi Road, Shangtang Village
Shitan Town, Zengcheng District
Guangzhou, Guangdong 511328 China

MODEL INFO

6800A/B
Polyurethane (PUR), furnished as two liquid components

FLAMMABILITY PROPERTIES	额定值	测试方法
Flammability		ANSI/UL 94
1.5 mm, Color: WT, BK	V-0	
3.0 mm, Color: WT, BK	V-0	
6.0 mm, Color: WT, BK	V-0	
10.0 mm, Color: WT, BK	V-0	
ISO/IEC FLAMMABILITY PROPERTIES	额定值	测试方法
Flammability		IEC 60695-11-10
1.5 mm, Color: WT, BK	V-0	
3.0 mm, Color: WT, BK	V-0	
6.0 mm, Color: WT, BK	V-0	
10.0 mm, Color: WT, BK	V-0	
THERMAL PROPERTIES	额定值	测试方法
Relative Thermal Index - Electrical Strength		UL 746B
1.5 mm	50 °C	

3.0 mm	50 °C	
6.0 mm	50 °C	
10.0 mm	50 °C	
Relative Thermal Index - Mechanical Impact		UL 746B
1.5 mm	50 °C	
3.0 mm	50 °C	
6.0 mm	50 °C	
10.0 mm	50 °C	
Relative Thermal Index - Mechanical Strength		UL 746B
1.5 mm	50 °C	
3.0 mm	50 °C	
6.0 mm	50 °C	
10.0 mm	50 °C	

Report Date: 2012-12-21
Revision Date: 2016-08-15

并不是所有出现在本数据库中的公司名称和产品都满足了UL 跟踪检验服务的要求。只有带有 UL 标志的产品，才应该被视为经过 UL 认证，并满足UL 跟踪检验服务的要求。注意查看产品上的标志。

UL 允许在线认证目录中所含材料的复制遵循以下条件：1.指南信息、装配、构造、设计、系统和/或认证（文件）必须在不篡改任何数据（或图纸）的情况下完整且无误导性地呈现。2.“经 UL 允许从在线认证目录转载”声明必须出现在所摘取材料的邻近位置。此外，转载材料必须包含以下格式的版权声明：“©2024 UL LLC.”